



Ubiquiti Switch USW-PRO-48-POE, Type L3, Rack, 48x10Base-T 100Base-TX 1000Base-T, 4xSFP, PoE+ ports 48, 600 Watts

Tootekood: **USW-PRO-48-POE** · Tootja: **Ubiquiti** · EAN: **817882027656** · Laos: 13 tk

Põhiandmed

LED-indikaatorid	Activity/Link/PoE/Speed/System
Mudeli nimi	USW-PRO-48-POE
Kommutaatori tüüp	Managed
RJ-45 Etherneti portide arv	48
RJ-45 Etherneti portide tüüp	Gigabit Ethernet (10/100/1000)
Võrgustandardid	IEEE 802.3af/IEEE 802.3at

Kirjeldus

Second-Generation UniFi SwitchingWe've redesigned our UniFi Switches from the ground up.

Near Silent CoolingOur new airflow design reduces the need for fan usage.

Powerful Hardware and SoftwareUniFi Switches offer a variety of features, including 10G SFP+ ports, PoE+ or PoE++ support, and Layer 3* switching capabilities.

Redundant Power SystemUniFi SmartPower RPS, USP-RPS, is our PSU failover system.

Power Supply FailureIn the event of a UniFi switch power supply failure, the USP-RPS automatically supplies redundant power to the failed device.

UniFi SmartPowerOne UniFi SmartPower device can support up to 6 devices until the failed device is replaced.

Touchscreen DisplayThe 1.3" touchscreen display allows easy monitoring and quick troubleshooting.

Tehnilised andmed

Üldandmed

Värv

Hõbedane

LED-indikaatorid	Activity/Link/PoE/Speed/System
Mudeli nimi	USW-PRO-48-POE
Võrk	
Kommutaatori tüüp	Managed
RJ-45 Etherneti portide arv	48
RJ-45 Etherneti portide tüüp	Gigabit Ethernet (10/100/1000)
Võrgustandardid	IEEE 802.3af/IEEE 802.3at
10G tugi	Jah
Kommutatsioonivõimsus	176 Gbit/s
Jumbo-kaadrite tugi	Jah
Power over Ethernet (PoE)	Jah
Toide ja energia	
Toiteplokk kaasas	Jah
Sisendpinge (AC)	100 - 240 V
Sisendsagedus (AC)	50 - 60 Hz
Ergonoomika ja kinnitus	
Rackpaigaldus	Jah
Möödud ja kaal	
Laius	442.4 mm
Sügavus	399.6 mm
Kõrgus	43.7 mm
Kaal	6250 g
Töötingimused	
Töötemperatuur	-5 - 40 °C
Töötamise suhteline õhuniiskus	10 - 90 %
Sertifikaadid	
Sertifikaat	CE, FCC, IC
Muu	
Switch layer	L2/L3
SFP+ module slots quantity	4

Port mirroring	Jah
Full duplex	Jah
Auto MDI/MDI-X	Jah
Auto-sensing	Jah
Flow control support	Jah
Spanning tree protocol	Jah
VLAN support	Jah
Throughput	88000 Mpps
Forwarding rate	130.944 Mpps
Static route	Jah
DHCP features	DHCP server
Authentication type	IEEE 802.1x,RADIUS
Vormitegur	1U
Number of power supply units	1
DC input voltage	44 - 57 V
Input current	11.54 A
Power over Ethernet plus (PoE+) ports quantity	40
Power over Ethernet (PoE) power per port	64 W
Total Power over Ethernet (PoE) budget	600 W
Tootja garantii	12 kuud