

MikroTik Access Point 1200 Mbit s, LHG-5AXD

Tootekood: **LHG-5AXD** · Tootja: **MikroTik** · EAN: **4752224009654** · Laos: 26 tk

Põhiandmed

Tk pakendis	1 tk
Mudeli nimi	LHG 5 ax
Sisseehitatud protsessor	Jah
Flash-mälu	128 MB
Mälu (RAM)	256 MB
Maksimaalne andmeedastuskiirus	1200 Mbit/s

Kirjeldus

Need a fast, stable connection across large distances? Whether you’re bridging two buildings, connecting a remote site, or sharing your internet with nearby infrastructure — the new LHG Wi-Fi 6 series is built for the challenge. And here’s the best part: we’ve kept the same pricing as the previous generation. High performance, long range, and Wi-Fi 6 — all without breaking the budget.

The 802.11ax standard brings crucial improvements for long-distance wireless links — including better spectral efficiency, higher modulation rates (1024-QAM), and lower latency. That means stronger performance even in noisy environments and faster, more stable connections over a greater distance. Combined with WPA3 encryption and RouterOS v7, the LHG ax series is ready for the challenges of modern outdoor networking. Order yours today — and be ready too!

LHG 5 ax is compact, long-range CPE with a 24.5 dBi antenna. Perfect for links up to 20 km in most scenarios. Check related devices below for the XL version if you need a longer distance!

Tehnilised andmed

Üldandmed

Värv	Valge
Tk pakendis	1 tk
Mudel	LHG-5AXD
Mudeli nimi	LHG 5 ax

Jõudlus	
Sisseehitatud protsessor	Jah
Mäluseadmed	
Flash-mälu	128 MB
Mälu (RAM)	256 MB
Ühendused	
Maksimaalne andmeedastuskiirus	1200 Mbit/s
Võrk	
Etherneti LAN-i kiirused	10/100/1000 Mbit/s
Võrgustandardid	IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11n
Power over Ethernet (PoE)	Jah
Antenni tüüp	Internal
Toide ja energia	
DC-sisendi pesa	Jah
Maksimaalne energiatarve	5 W
Ergonoomika ja kinnitus	
Kinnituskomplekt	Jah
Töötingimused	
Töötemperatuur	-40 - 70 °C
Sertifikaadid	
Sertifikaat	CE, FCC, IC, EAC, ROHS
Muu	
2.4 GHz	Ei
5 GHz	Jah
Transmitting power	24 dBmW
Receiver sensitivity	-96, -80, -75, -70, -67
Power over Ethernet (PoE) type supported	Passive PoE
Placement	Pole
Antenna gain level (max)	24.5 dBi
PoE adapter included	Jah

Tootja garantii	12 kuud