

Eaton UPS 360 Watts, 700 VA, Wave form type Pure sinewave, LineInteractive, Phase 1phase, Desktop/pedestal, 5E700I

Tootekood: **5E700I** · Tootja: **Eaton** · EAN: **3553340704130** · Laos: 21 tk

Põhiandmed

Toitekaitse omadused	Over voltage/Under voltage
Toiteallika tüüp	AC
Laius	100 mm
Sügavus	288 mm
Kõrgus	148 mm
Kaal	4300 g

Kirjeldus

Eaton 5E Gen2 delivers efficient, affordable power protection for critical applications in both residential and professional settings.

Power protectionEaton 5E Gen2 UPS protects application and data against power loss.Double-boost Automatic Voltage Regulation (AVR) technology regulates grid fluctuations (under and overvoltage) to save battery power in the event of power outage.A wide product range covers the power requirements of many IT devices.Auto-restart function enables the UPS to restart automatically when mains power recovers after a total battery discharge.

Easy integrationEaton 5E Gen2 implements national outlet formats (FR, DIN/IT, BS and IEC) to make application connection and protection easy.Fanless design up to 1200VA ensures silent operation in residential settings.Compact housing makes it easy to integrate in home or office.Easily manage your UPS from your PC (on USB models):Integrates automatically with Windows / MacOS / Linux power management for safe system shutdown.Analyse energy usage and manage UPS parameters with Eaton UPS Companion software.

Tehnilised andmed

Üldandmed

Värv	Must

Mudel	5E700I
Toide ja energia	
Toitekaitse omadused	Over voltage/Under voltage
Toiteallika tüüp	AC
Mõõdud ja kaal	
Laius	100 mm
Sügavus	288 mm
Kõrgus	148 mm
Kaal	4300 g
Töötingimused	
Müratase	25 dB
Töötemperatuur	0 - 40 °C
Sertifikaadid	
Vastavussertifikaadid	Low Voltage Directive (LVD)/RoHS/WEEE
Keskkonnanõuetele vastavus	Jah
Sertifikaat	EN IEC 62040-1:2019; EN 62040-2:2006; IEC 62040-2: 2016, IEC 62040-3: 2021; CE; EAC; UKCA; Cm; Ukr
Muu	
UPS topology	Line-Interactive
Output power capacity	0.7 kVA
Output power	360 W
Input operation voltage (min)	220 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Audible alarm(s)	Jah
Audible alarm modes	Battery replacement
Auto-restart	Jah
AC outlet types	C13 coupler
AC outlets quantity	4 AC outlet(s)

Automatic battery test	Jah
Cold start	Jah
Vormitegur	Tower
Juhtimise tüüp	Buttons
Tootja garantii	24 kuud