

Axagon Cable USB-C to USB-C 2M 240W braid blk BUCM2-CM20AB

Tootekood: **BUCM2-CM20AB** · Tootja: **Axagon** · EAN: **8595247907417** · Laos: 20 tk

Põhiandmed

Pakendi tüüp	Bag
Tk pakendis	1 tk
Mudeli nimi	BUCM2-CM20AB Data and charging USB 480Mbps cable 2 m. PD 240W, 5A. Black braided
Kaabli pikkus	2 m
USB versioon	USB 2.0
Ühendus 1	USB C

Kirjeldus

Premium connection USB-C USB-C Data and Charging AXAGON BUCM2-CM20AB CHARGE cable with USB-C male connectors at both ends. The cable is designed especially for charging and powering computers, monitors, laptops, phones, tablets and other devices. It also supports data transfer speeds of up to 480 Mb/s.

The cable has implemented the latest specification of Power Delivery 3.1 charging technology. This technology delivers, among other things, a power output of 240W which is more than double that of Power delivery 3.0, which delivers 100W. You can use not only the (Standard Power Range SPR) for voltages of 5, 9, 15 and 20V with a current of 5A, but also sufficient power in fixed voltages of 28, 36 and 48V with a maximum current of 5A (Extended Power Range - EPR). Thanks to the new PD 3.1 technology, you can also use the cable to power devices with much more power, such as gaming laptops, 4K monitors, power tools or the increasingly popular e-scooters. To identify the cable and its current capabilities, the cable has an integrated E-Mark chip. The cable is also compatible with Quick Charge, PPS, Samsung AFC and SFC, Apple, SMART and other charging technologies.

Tehnilised andmed

Üldandmed

Värv	Must

Pakendi tüüp	Bag
Tk pakendis	1 tk
Päritoluriik	Hiina
Mudel	BUCM2-CM20AB
Mudeli nimi	BUCM2-CM20AB Data and charging USB 480Mbps cable 2 m. PD 240W, 5A. Black braided
Ühendused	
Kaabli pikkus	2 m
USB versioon	USB 2.0
Ühendus 1	USB C
Ühendus 2	USB C
Ühenduse 1 sugu	Male
Ühenduse 2 sugu	Male
Ühenduspesa 1 tüüp	Sirge
Ühenduspesa 2 tüüp	Sirge
Kontaktide katend	Kuldne
Maksimaalne andmeedastuskiirus	0.48 Gbit/s
Kaabli tüüp	Round cable
Toide ja energia	
Kiirlaadimine	Jah
USB Power Delivery (USB PD)	Jah
USB Power Delivery kuni	240 W
Sisendpinge	48 V
Mõõdud ja kaal	
Kaabli läbimõõt	4.6 mm
Kaal	50 g
AWG juhtme suurus	22/30
Kaabli mantli materjal	Thermoplastic elastomer (TPE)
Pakendi laius	205 mm
Pakendi sügavus	130 mm
Pakendi kõrgus	15 mm

Pakendi kaal	77 g
Sertifikaadid	
Vastavussertifikaadid	CE/RoHS
Sertifikaat	CE, RoHS
Muu	
Connector material	Nickel
Cable jacket type	Braided
Conductor material	Oxygen-Free Copper (OFC)
Connector shield material	Copper
Connector shielding	Jah
Connector housing material	Metall
USB Power Delivery revision	3.1
Compatible products	computers, monitors, laptops, phones, tablets and other devices
Input current (max)	5 A
Tootja garantii	24 kuud