



## Lian Li Power Supply edge gold 750, SFX, PC, 100 - 240 V, 750 W, G9P.EG0750G.B000.EU

Tootekood: **G9P.EG0750G.B000.EU** · Tootja: **Lian Li** · EAN: **4718466016430** ·  
Laos: 100 tk

### Põhiandmed

|                    |                                  |
|--------------------|----------------------------------|
| Kasutusotstarve    | PC                               |
| Kaablid kaasas     | CPU,PCIe,Peripheral (Molex),SATA |
| Mudeli nimi        | EDGE GOLD 750                    |
| Sisendpinge (AC)   | 100 - 240 V                      |
| Sisendsagedus (AC) | 50/60 Hz                         |
| Laius              | 86 mm                            |

### Kirjeldus

Блок живлення ATX3.1 Lian Li Edge Gold 750W (G9P.EG0750G.B000.EU)

THE “POWER” FOR DUAL CHAMBER CASES

The EDGE Gold PSU series features a unique L-shape design, a removable USB and fan PWM hub, longer modular cables, and a conveniently removable dust filter. Experience efficient cable management in a dual chamber or tower chassis that blends aesthetics and convenience in your PC build.

AVAILABLE IN 2 COLORS AND 4 WATTAGES

Offering versatile options, the EDGE Gold PSU is available in multiple configurations with or without a USB hub to meet different power needs and match the components' colors.

Introducing the world's first PSU with a detachable USB and PWM fan hub that also functions independently, and that features a removable magnetic dust filter. This unique form factor reorients the connectors outward, simplifying cable management and ensuring a clean, organized build.

### Tehnilised andmed

#### Üldandmed

|                 |    |
|-----------------|----|
| Kasutusotstarve | PC |
|-----------------|----|

|                                             |                                  |
|---------------------------------------------|----------------------------------|
| Värv                                        | Must                             |
| Kaablid kaasas                              | CPU,PCIe,Peripheral (Molex),SATA |
| Mudeli nimi                                 | EDGE GOLD 750                    |
| <b>Toide ja energia</b>                     |                                  |
| Sisendpinge (AC)                            | 100 - 240 V                      |
| Sisendsagedus (AC)                          | 50/60 Hz                         |
| <b>Möödud ja kaal</b>                       |                                  |
| Laius                                       | 86 mm                            |
| Sügavus                                     | 182 mm                           |
| Kõrgus                                      | 150 mm                           |
| <b>Muu</b>                                  |                                  |
| Total power                                 | 750 W                            |
| Maximum input current (@110V)               | 9 A                              |
| Maximum input current (@220V)               | 4.5 A                            |
| Combined power (+3.3V)                      | 120 W                            |
| Combined power (+12V)                       | 744 W                            |
| Combined power (+5V)                        | 120 W                            |
| Efficiency                                  | 90.52 %                          |
| Motherboard power connector                 | 24-pin ATX                       |
| Motherboard power cable length              | 620 mm                           |
| Number of SATA power connectors             | 3                                |
| SATA power cable length                     | 300/400 mm                       |
| Peripheral (Molex) power connectors (4-pin) | 4                                |
| Peripheral (Molex) power cable length       | 500 mm                           |
| EPS power connector (8-pin)                 | Jah                              |
| PCI Express power connectors (6+2 pin)      | 1                                |
| PCI Express power connectors (8-pin)        | 1                                |
| PCI Express power cable length              | 400 mm                           |
| CPU P4 connector (4-pin)                    | 1                                |
| CPU power connector (4+4 pin)               | Jah                              |

|                                     |                              |
|-------------------------------------|------------------------------|
| CPU power cable length              | 750 mm                       |
| ATX Power connector (24-pin)        | Jah                          |
| Cabling type                        | Fully-Modular                |
| 80 PLUS certification               | 80 PLUS Gold                 |
| Supported motherboard form factors  | ATX                          |
| Power supply unit (PSU) form factor | SFX                          |
| Silent mode                         | Jah                          |
| Noise level                         | 30.9 dB                      |
| Bearing technology                  | FDB                          |
| Fan diameter                        | 120 mm                       |
| Safety                              | OCP/ OPP/ UVP/ OVP/ OTP/ SCP |
| Tootja garantii                     | 24 kuud                      |