



Lian Li Power Supply SP0750G.W, SFX, PC, 100 - 240 V, 750 W, G9P.SP0750G.W000.EU

Tootekood: **G9P.SP0750G.W000.EU** · Tootja: **Lian Li** · EAN: **4718466018434** ·
Laos: 50 tk

Põhiandmed

Kasutusotstarve	PC
Sisse/välja lüliti	Jah
Mudeli nimi	SP0750G.W
Jahutuse tüüp	Active
Ventilaatorite arv	1 fan(s)
Sisendpinge (AC)	100 - 240 V

Kirjeldus

Блок живлення SFX Lian Li 80 PLUS Gold 750W White (G9P.SP0750G.W000.EU)

PERFORMANCE SFX FORM FACTOR POWER SUPPLY The SP V2 Gold is a stylish high-performance PSU that perfectly fits small-form-factor PCs while supporting power-hungry components.

AVAILABLE IN TWO COLORS & TWO WATTAGES Choose the fully modular SFX PSU in black or white, with 850W or 750W options to perfectly match your build.

COMPACT SIZE, BIG PERFORMANCE Measuring 125 × 100 × 63.5 mm, this compact PSU saves valuable space inside the builds without compromising on power delivery.

80 PLUS GOLD CERTIFICATE With 80 PLUS Gold certification, the SP V2 Gold delivers over 90% efficiency at 50% system load under 115V AC input conditions, ensuring high energy efficiency with stable power delivery and minimal energy loss.

ATX 3.1 READY WITH 12V-2×6 CONNECTOR The SP V2 Gold features a next-gen 12V-2×6 power connector compliant with the latest ATX 3.1 specification, providing direct support for PCIe 5.0 graphics cards and addressing the growing power demands of modern systems.

Tehnilised andmed

Üldandmed

Kasutusotstarve	PC
Värv	Valge
Sisse/välja lüliti	Jah
Mudeli nimi	SP0750G.W
Jõudlus	
Jahutuse tüüp	Active
Ventilaatorite arv	1 fan(s)
Toide ja energia	
Sisendpinge (AC)	100 - 240 V
Sisendsagedus (AC)	50/60 Hz
Mõõdud ja kaal	
Laius	125 mm
Sügavus	100 mm
Kõrgus	63.5 mm
Töötingimused	
Töötemperatuur	0 - 40 °C
Muu	
Total power	750 W
Input current	5 - 10 A
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	100 W
Combined power (+12V)	744 W
Combined power (+5V)	100 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	20 A
Max output current (+12V)	62 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A

Efficiency	90 %
Power protection features	No load operation/Over current/Over power/Over voltage/Short circuit/Surge & inrush protection (SIP)/Under temperature/Under voltage
Motherboard power connector	20+4 pin ATX
Motherboard power cable length	350 mm
Number of SATA power connectors	7
SATA power cable length	350 mm
Peripheral (Molex) power connectors (4-pin)	1
EPS power connector (8-pin)	Jah
PCI Express power connectors (6+2 pin)	2
PCI Express power connectors (8-pin)	1
PCI Express power cable length	400 mm
CPU power connector (4+4 pin)	Jah
CPU power cable length	600 mm
Cabling type	Fully-Modular
80 PLUS certification	80 PLUS Gold
Power supply unit (PSU) form factor	SFX
ATX version	3.1
Noise level	32.5 dB
Bearing technology	FDB
Fan diameter	92 mm
Fan speed	0 - 3000 RPM
Tootja garantii	24 kuud