



Lindy Cable HDMI-HDMI 2M anthra 36963

Tootekood: **36963** · Tootja: **Lindy** · EAN: **4002888369633** · Laos: 29 tk

Põhiandmed

Pakendi tüüp	Polybag
Tk pakendis	1 tk
Maksimaalne eraldusvõime	4096 x 2160 pixels
Kaabli pikkus	2 m
Ühendus 1	HDMI Type A (Standard)
Ühenduse 1 sugu	Male

Kirjeldus

From the Lines cable connectivity concept developed by Lindy, Anthra Line HDMI cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line HDMI cables are premium connections that feature triple shielded with 30AWG copper conductors with for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 8bit are supported. Anthra Line HDMI cables are also capable of transmitting 32 channel audio and Dolby® True HD.

The HDMI 2.0 specification is supported for 18Gbps bandwidth capacity in cable lengths up to 5m.

Anthra Line HDMI cables are available in lengths from 0.3m to 5m.

Tehnilised andmed

Üldandmed

Värv	Black/Grey
Pakendi tüüp	Polybag
Tk pakendis	1 tk

Ekraan

Maksimaalne eraldusvõime	4096 x 2160 pixels
--------------------------	--------------------

Ühendused

Kaabli pikkus	2 m
Ühendus 1	HDMI Type A (Standard)
Ühenduse 1 sugu	Male
Ühendus 2	HDMI Type A (Standard)
Ühenduse 2 sugu	Male
HDMI versioon	2.0

Töötingimused

Töötemperatuur	-10 - 80 °C
Hoiustamise temperatuur	-10 - 80 °C

Sertifikaadid

Sertifikaat	RoHS, REACH, UL, ATC
-------------	----------------------

Muu

Connector 1 form factor	Sirge
Connector 2 form factor	Sirge
3D	Jah
Supported graphics resolutions	4096 x 2160
Supported video modes	1080p
Dolby technologies	Dolby TrueHD/DTS-HD Master Audio
Audio Return Channel (ARC)	Jah
HDMI Ethernet channel	Jah
Data transfer rate	18 Gbit/s
AWG wire size	30
Contact material	Phosphor copper
Connector contacts plating	Kuldne
Connector housing material	Polyvinyl chloride (PVC)
Connector material	Kuldne
Cable material	Copper
Cable type	Round cable
Cable jacket material	Polyvinyl chloride (PVC)

Shield material	Copper
Bending radius (min)	48 mm
Colour sampling	4:4:4
Nominal attenuation	300kHz-825MHz 5dB, 825MHz-2.475GHz 5dB, 2.475GHz-4.125GHz 12dB, 4.125GHz-5.1GHz 20dB
Cable diameter	6 mm
Connector 1 dimensions (WxDxH)	20 x 34.2 x 10.9 mm
Connector 2 dimensions (WxDxH)	20 x 34.2 x 10.9 mm
Tootja garantii	120 kuud