



Dahua Wrl camera 5MP bullet Wi-Fi F5D-IL-0280B

Tootekood: **F5D-IL-0280B** · Tootja: **Dahua** · EAN: **6939554980404** · Laos: 10 tk

Põhiandmed

Tüüp	IP security camera
Korpuse materjal	Metal/Plastic
Toetatud mobiilsed operatsioonisüsteemid	Android/iOS
Mudeli nimi	DH-IPC-HDW1230T1-S4
Maksimaalne eraldusvõime	1920 x 1080 pixels
Sensori tüüp	CMOS

Kirjeldus

With features of simple installation, easy operation, and high performance-cost ratio, Dahua Entry Series camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises.

Tehnilised andmed

Üldandmed

Tüüp	IP security camera
Värv	Valge
Korpuse materjal	Metal/Plastic
Toetatud mobiilsed operatsioonisüsteemid	Android/iOS
Mudel	F5D-IL-0280B
Mudeli nimi	DH-IPC-HDW1230T1-S4

Ekraan

Maksimaalne eraldusvõime	1920 x 1080 pixels
--------------------------	--------------------

Jõudlus

Sensori tüüp	CMOS
Toetatud videovormingud	H.264/H.265/M-JPEG
Mäluseadmed	
Mälu (RAM)	64 MB
Ühendused	
Ühendustehnoloogia	Juhtmega
Võrk	
Ethernet LAN	Jah
Etherneti liidese tüüp	Fast Ethernet
Wi-Fi	Ei
Bluetooth	Ei
Ethernet (RJ-45) portide arv	1
Toide ja energia	
Toiteallika tüüp	DC,PoE
Tüüpiline energiatarve	4.3 W
Ergonoomika ja kinnitus	
Paigaldustüüp	Ceiling
Kallutusnurga vahemik	0 - 78 °
Möödud ja kaal	
Kõrgus	85.5 mm
Kaal	240 g
Pakendi kaal	370 g
Töötingimused	
IP-kaitseklass	IP67
Töötemperatuur	-40 - 60 °C
Hoiustamise temperatuur	-40 - 60 °C
Töötamise suhteline õhuniiskus	0 - 95 %
Hoiustamise suhteline õhuniiskus	0 - 95 %
Muu	
Placement supported	Indoor & outdoor

Wide Dynamic Range (WDR)	Jah
Day/night mode	Jah
Infrared (IR) cut-off filter	Jah
Vormitegur	Dome
Camera pan control	Jah
Camera tilt control	Jah
Minimum illumination	0.01 lx
Angle of rotation	360 °
Lens viewing angle, horizontal	105 °
Lens viewing angle, vertical	57 °
Lens viewing angle, diagonal	125 °
Pan range	0 - 355 °
White balance	Auto/Manual/Natural/Outdoor
Camera shutter type	Electronic
Camera shutter speed	1/3-1/100000 s
Adjustment shutter speed	Auto/Manual
Number of sensors	1
Optical sensor size	1/2.7 "
Progressive scan	Jah
Number of effective pixels (H x V)	1920 x 1080 pixels
Number of lenses	1
Detect distance	37.3 m
Observe distance	14.9 m
Recognize distance	7.5 m
Fixed focus	Jah
Identify distance	3.7 m
Maximum aperture number	2
Closest focusing distance	0.5 m
Fixed focal length	2.8 mm
Night vision	Jah
Night vision distance	30 m

LED type	IR
Number of illumination LEDs	1
Total megapixels	2 MP
Supported graphics resolutions	1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/352 x 240/352 x 288/640 x 480 (VGA)/704 x 480/704 x 576
Supported video modes	1080p/720p
Frame rate	30 fps
Noise reduction	Jah
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Back Light Compensation (BLC)	Jah
Digital Wide Dynamic Range (DWDR)	Jah
Highlight Compensation (HLC)	Jah
Privacy masking	Jah
Region of Interest (ROI) encoding	Jah
Smart IR	Jah
Supported network protocols	IPv4; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS; NTP; Multicast
Built-in HDD	Ei
ROM capacity	16 MB
Motion sensor	Jah
Web browser	Jah
Management software	Smart PSS; DSS; DMSS
DC output voltage	12
Diameter	109 mm
Number of cameras	1
Tootja garantii	36 kuud