

Montech CPU cooler multi socket black hyperflow SILENT240(B)

Tootekood: **HYPER FLOW SILENT 240 (B)** · Tootja: **Montech** · EAN: **4710562745399** · Laos: 50 tk

Põhiandmed

Tüüp	All-in-one liquid cooler
Sobiv kasutuskoht	Processor
Tk pakendis	1 tk
Mudeli nimi	HyperFlow Silent 240
Ventilaatorite arv	2 fan(s)
Ventilaatori läbimõõt	120 mm

Kirjeldus

Building on the success of the HyperFlow ARGB in 2024, we took community feedback to heart and developed the HyperFlow Silence—offering even better cooling with ultra-quiet performance. Let’s dive into what’s improved!

Whisper-Quiet Innovation for Ultimate FocusDesigned for peak performance, the 3100RPM pump ensures rapid heat dissipation, keeping your system cool when it matters most. The cold plate is also pre-applied with thermal paste for easy and effective installation.

Whisper-Quiet Innovation with Metal PRO 12 SilentThe Metal PRO 12 Silent builds upon the original Metal PRO 12, delivering the same powerful 2200RPM performance while cutting noise by 13.9% for a significantly quieter operation.

Effortless Cooling for Demanding TasksEngineered to handle the heat of high-performance CPUs effortlessly27mm Fin Stack with 20FPI

Minimalist EleganceBlack or white, circle swirl pattern, delivers a sleek, ARGB-free design for a professional, minimalist look.

Tehnilised andmed

Üldandmed

Tüüp	All-in-one liquid cooler

Sobiv kasutuskoht	Processor
Tk pakendis	1 tk
Värv	Must
Mudeli nimi	HyperFlow Silent 240
Jõudlus	
Toetatud protsessoripesad	LGA 1150 (Socket H3)/LGA 1151 (Socket H4)/LGA 1155 (Socket H2)/LGA 1156 (Socket H)/LGA 1200 (Socket H5)/LGA 1700/LGA 2011 (Socket R)/LGA 2066/Socket AM3/Socket AM4/Socket AM5
Ventilaatorite arv	2 fan(s)
Mõõdud ja kaal	
Ventilaatori läbimõõt	120 mm
Töötingimused	
Maksimaalne õhuvool	72.3 cfm
Muu	
Airflow	129.5 m³/h
Maximum air pressure	3.12 mmH2O
Pulse-width modulation (PWM) support	Jah
Bearing type	Fluid Dynamic Bearing (FDB)
Fan noise level (max)	24.8 dB
Pump noise level	23 dB
Pump connector	4-pin
Fan speed (max)	2200 RPM
Fan speed (min)	800 RPM
Pump motor speed	3100 RPM
Radiator material	Aluminum
Fan connector	4-pin
Fan power consumption	2.16 W
Pump power consumption	3.6 W
Fan current	0.18 A
Pump current	300 mA

Hub voltage	5 V
Radiator width	277 mm
Radiator depth	27 mm
Radiator height	120 mm
Tube length	400 mm
Pump width	68.8 mm
Pump depth	68.8 mm
Pump height	53 mm
Fan dimensions (W x D x H)	120 x 120 x 28 mm
Tootja garantii	72 kuud