



Toshiba HDD S300, 6 TB, Serial ata, Buffer 256 MB, 5400 rpm, 3.5", HDWT860UZSVA

Tootekood: **HDWT860UZSVA** · Tootja: **Toshiba** · Laos: 50 tk

Põhiandmed

Tüüp	HDD
Sobib seadmele	Surveillance system
Liides	Serial ATA
Tüüpiline energiatarve	4.84 W
Laius	101.85 mm
Sügavus	26.1 mm

Kirjeldus

EMEA Region, Toshiba Storage Solutions – With surveillance systems, nothing but the best is good enough. The Toshiba 3.5-inch S300 is built to meet the highest demands. With support for up to 64 high-resolution surveillance video cameras simultaneously and up to 6 TB capacity, it brings everything into clear view. Each S300 is built with the highest-quality components and has passed rigorous tests to ensure 24 x 7 reliability and performance. That's Toshiba quality you can trust under the harshest working conditions.

- Surveillance Digital Video Recorders (sDVR)- Surveillance Network Video Recorders (sNVR)- Hybrid sDVR (analog and IP)

Reliability is a function of component quality and testing. The S300 takes it to a new level, using optimised components to deliver the clear detail from up to 64 video cameras at the same time. Rigorous testing provides performance you can trust day in, day out.

Tehnilised andmed

Üldandmed

Tüüp	HDD
Sobib seadmele	Surveillance system
Mudel	Toshiba S300 6TB (HDWT860UZSVA)

Ühendused

Liides

Serial ATA

Toide ja energia

Tüüpiline energiatarve 4.84 W

Mõõdud ja kaal

Laius 101.85 mm

Sügavus 26.1 mm

Kõrgus 147 mm

Kaal 680 g

Töötingimused

Töötemperatuur 0 - 70 °C

Hoiustamise temperatuur -40 - 70 °C

Sertifikaadid

Vastavussertifikaadid CE

Muu

HDD capacity 6000 GB

HDD speed 5400 RPM

Storage drive buffer size 256 MB

HDD size 3.5 "

HDD interface transfer rate 6 Gbit/s

HDD sustained transfer rate 241 MiB/s

Average latency 5.56 ms

Uncorrectable Bit Error Rate (UBER) < 1 per 10¹⁴ bits read

Advanced Format (AF) Jah

Rotational Vibration (RV) sensors Jah

Shock sensor Jah

24/7 operation Jah

Native Command Queuing (NCQ) Jah

Start/stop cycles 600000

Workload rate limit 180 TB/year

Noise level (idle) 24 dB

Mean time to failure (MTTF)	1000000 h
Power consumption (idle)	2.81 W
Operating voltage	5 / 12 V
Operating shock	70 G
Non-operating shock	250 G
Doesn't contain	Halogen
Sustainability compliance	Jah
Toshiba Dynamic Cache Technology	Jah
Toshiba Stable Platter Technology	Jah
HDD Family name	S300
Tootja garantii	36 kuud