

ASRock Mainboard AMD A520, SAM4, Micro-ATX, Memory DDR4, Memory slots 2, 1xPCI-Express 3.0 1x, 1xPCI-Express 3.0 16x, 1xM.2, 1x15pin D-sub, 1xHDMI, 2xAudio-In, 1xAudio-Out, 2xUSB 2.0, 4xUSB 3.2, 1xPS/2, 1xRJ45, A520M-HVS

Tootekood: **A520M-HVS** · Tootja: **ASRock** · EAN: **4710483932311** · Laos: 100 tk

Põhiandmed

Sobib seadmele	PC
Kaablid kaasas	SATA
Emaplaadi kiibistik	AMD A520
Emaplaadi vormitegur	micro ATX
Heliväljundi kanalid	7.1 channels
Emaplaadi kiibistikuperekond	AMD

Kirjeldus

A520 MOTHERBOARD FOR EVERYONEAll Essentials You Need For Computing

Ultra M.2 32Gb/s (PCIe Gen3 x4 & SATA3)The PCIe Gen3 x4 Ultra M.2 interface pushes data transfer speeds up to 32Gb/s. In addition, it also supports SATA3 6Gb/s M.2 modules.

HDMI 4k @60HzSupports the most recent HDMI 4K 60Hz graphics output specification. With the larger bandwidth and increased frame rate, the motion on your screen becomes more fluid and less blurry.

Dual Graphics OutputsComplete with two types of most used connectors! Packed with a D-Sub + HDMI combo, you have more graphics output options now.

Full Spike ProtectionSome sensitive digital components on the motherboard are vulnerable to power surges, the excessive current may cause your system to malfunction immediately. ASRock Full Spike Protection includes various technologies to prevent your motherboard’s components from being damaged by these unexpected voltage spikes.

Tehnilised andmed

Üldandmed	
Sobib seadmele	PC
Kaablid kaasas	SATA
Jõudlus	
Emaplaadi kiibistik	AMD A520
Emaplaadi vormitegur	micro ATX
Heliväljundi kanalid	7.1 channels
Emaplaadi kiibistikuperekond	AMD
Protsessori tootja	AMD
Protsessori pesa	Socket AM4
Ühilduvad protsessorisarjad	AMD Ryzen 3000 Series
Graafikakaart	Radeon Vega
Mäluseadmed	
Toetatud mälutüübid	DDR4-SDRAM
Mäluavade arv	2
Mäluavade tüüp	DIMM
Mälukanalid	Dual-channel
ECC ühilduvus	Non-ECC
Maksimaalne mälumaht	64 GB
Puhverdamata mälu	Jah
Toetatud ketaste liidesed	M.2,SATA III
Toetatud kõvaketaste arv	5
Heli	
Mikrofonisisend	Jah
Ühendused	

USB 2.0 pesad	2
USB 3.2 Gen 1 pesad	1
Esipaneeli heliühendus	Jah
ATX toitepistik (24-pin)	Jah
Protsessoriventilaatori pistik	Jah
USB 2.0 portide arv	2
USB-A (USB 3.2 Gen 1) portide arv	4
VGA (D-Sub) portide arv	1
HDMI portide arv	1
Võrk	
Ethernet (RJ-45) portide arv	1
Ethernet LAN	Jah
Etherneti liidese tüüp	Gigabit Ethernet
Wi-Fi	Ei
Mõõdud ja kaal	
Laius	230 mm
Sügavus	201 mm
Muu	
Supported memory clock speeds	2133/2400/2666/2933/3200/3466/3600/3733/3800/3866/4000/4133/4200/4266/4333 MHz
Graphics card family	AMD
Number of chassis fan connectors	2
Number of COM connectors	1
PS/2 ports quantity	1

LAN controller	Realtek RTL8111H
Wake-on-LAN ready	Jah
PCI Express x1 (Gen 3.x) slots	1
PCI Express x16 (Gen 3.x) slots	1
BIOS-i tüüp	UEFI AMI
Drivers included	Jah
Tootja garantii	24 kuud