



Dahua Net video recorder 32CH NVR5232-EI2

Tootekood: **NVR5232-EI2** · Tootja: **Dahua** · EAN: **6937552405141** · Laos: 8 tk

Põhiandmed

HDMI portide arv	1
USB 2.0 portide arv	2
Ethernet (RJ-45) portide arv	1
Etherneti LAN-i kiirused	10/100/1000 Mbit/s
Laius	375 mm
Sügavus	284.8 mm

Kirjeldus

32CH 1U 2HDDs WizSense Network Video Recorder > Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats. > Max. decoding capability: 40 × 1080p@30 fps or 10 × 8MP@30 fps. > Max. 448/448/448 Mbps incoming/recording/outgoing bandwidth. > Supports IP cameras with a resolution up to 32 MP. > Supports 8K HDMI output. > Supports N+M cluster and iSCSI. > AI by Recorder supports 4-channel face detection and recognition, up to 20 face databases and 30,000 face images; 4-channel video metadata; 8-channel perimeter protection; 16-channel SMD Plus; 4-channel AcuPick. > AI by Camera supports face detection and recognition, perimeter protection, SMD, metadata, AcuPick, ANPR, stereo analysis, heat map, people counting, PPE detection, smart object detection and smart sound detection. > Supports EPTZ, and one-click arming and disarming.

Tehnilised andmed

Üldandmed

Mudel NVR5232-EI2

Ühendused

HDMI portide arv	1
USB 2.0 portide arv	2

Võrk

Ethernet (RJ-45) portide arv	1
------------------------------	---

Etherneti LAN-i kiirused	10/100/1000 Mbit/s
--------------------------	--------------------

Mõõdud ja kaal

Laius	375 mm
Sügavus	284.8 mm
Kõrgus	56 mm
Kaal	1550 g

Töötingimused

Töötemperatuur	-10 °C to +55 °C
Hoiustamise temperatuur	-20 °C to +60 °C

Muu

Video input channels	32 channels
Alarm input channels	4
Alarm output channels	2
Number of HDDs supported	2
HDD interface	Serial ATA
VGA (D-Sub) output ports	1
Audio RCA inputs	1
Audio RCA outputs	1
RS-232 interface	Jah
RS-232 ports	1
RS-485 ports	1
Tootja garantii	36 kuud